


Zpětné ventily z materiálu PVDF



Zpětný ventil kuželový, PVDF, typ S4, s pružinou

- Těsnění: FPM
- Max. provozní tlak: d 16-d 75 PN16, d 90 PN10, d 110 PN6
- Pružina: poteflonovaná

Ø	Objímky Obj.č.	Nátrubky Obj.č.	Závit Obj.č.
DN10/d16-3/8"	12.1658	12.1676	12.1667
DN15/d20-1/2"	12.1659	12.1677	12.1668
DN20/d25-3/4"	12.1660	12.1678	12.1669
DN25/d32-1"	12.1661	12.1679	12.1670
DN32/d40-1 1/4"	12.1662	12.1680	12.1671
DN40/d50-1 1/2"	12.1663	12.1681	12.1672
DN50/d63-2"	12.1664	12.1682	12.1673
DN65/d75-2 1/2"	12.1665	12.1683	12.1674
DN80/d90-3"	12.1666	12.1684	12.1675
DN80/d110-4"	12.2350	12.2351	



SRIF-kulový zpětný ventil

O-kroužky FPM

d	E	L	H	PN	Váha	Objed.číslo
20	54	16	104	16	150	SRIF 02022
25	65	19	125	16	260	SRIF 02522
32	74	22	148	16	390	SRIF 03222
40	86	26	172	16	600	SRIF 04022

50	98	31	186	16	820	SRIF 05022
63	119	38	221	16	1420	SRIF 06322
